

Compact size Ideal for counter space

CP-Q3



Simple and elegant, with high optical mirror and sticks appearance
Internal important parts are with metal material
high printing speed, rapidly change supplies
With auto cutter, paper out alarm
Parallel, serial, USB, Ethernet Optional multiple interfaces
(supports two in one, or three in one)
Low noise, support high speed graphics and hardware fonts printing

Description

COLOURS



CP-Q3



INDUSTRIAL APPLICATIONS



Retail



Hospitality



Transportation



Government



Direct Store
Delivery



Postal and
Courier Services



Field Service



Field Sales

Model Numbers

Printer

Printing Method Direct Thermal

Printing Direction Line printing

Mechanism

Max Print Width 82.5mm ± 0.5 mm

Effective Print Width 72mm

Character Size Font A: 12 x 24 dots ;
Font B: 9 x 17 dots

Character per line Font A: 48 ;
Font B: 64

Printing Speed 260mm/sec

Printer Density 576 dots/line, 203dpi

Life 100 KM

Printer Head

Print font

ASCII code 13 international character set

Chinese Big 5 / GB123

Bar code

1D: UPC-A/ UPC-E/ JAN13(EAN13)/
JAN8(EAN8)/ CODE39/ Interleaved 2
of 5/ CODABAR/ CODE93/ CODE128

2D: QR CODE / PDF417

Cutter

Auto Cutter Full cut or Partial cut

Life Span 1,000,000 times

Driver

Win9X/WinME/Win2000/WinNT/WinXP, Win
Vista, Win7/WIN 8/Linux

Interface

Serial

Dsub 9 pin female connector,
default with 9600 or up to
115200 bps baud-rate (straight)

USB

USB 2.0 full-speed (HID signal)

Ethernet

10/100Base-T

Cash Drawer

DC 24V, 1A, RJ-11 socket

Print commands

ESC/POS

OPOS driver available

Input Buffer

256KB for NV Flash buffer
2048KB for Data receive buffer

SPI Flash Memory

4MB

Paper

Paper Width

82.5mm ± 0.5 mm

Roll diameter

Max. 83mm

Thickness

0.06 ~ 0.08mm

Environment

Operating

0°C ~ 45°C; 10%RH ~ 80%RH

Storage

-10°C ~ 60°C; 10%RH ~ 90%RH

Power supply

Input

100V AC ~ 220V AC, 50-60Hz
(≤ 1.5 A)

Output

DC +24V / 2.5A

Dimension

183(L) x 143.5(W) x 135mm (H)

Gross Weight

3.5Kgs

Black Mark

Supported

Sensor

Cover open sensor, Receipt
coming alarm, Error alarm sensor



QR code



1D Barcode



High Speed



Easy load