

POSWAY®



TP700



POSWAY TP700 is a high-speed 80mm Wi-Fi thermal receipt printer designed for seamless printing in retail, hospitality, and mobile businesses. With a rapid printing speed of 26mm per second, it ensures quick and efficient transaction processing, reducing customer wait times. Its dual-mode Wi-Fi (AP & STA) offers flexible connectivity, allowing easy integration with POS systems, tablets, and smartphones—perfect for both fixed and on-the-go setups. The built-in auto cutter ensures clean, precise receipt cuts, eliminating manual tearing and enhancing professionalism. Compact yet durable, the POSWAY TP700 is an ideal choice for businesses seeking a reliable, wireless thermal printer that combines speed, convenience, and advanced functionality.

Printer is ideal for a wide range of sectors requiring fast, reliable, and wireless printing solutions. In retail stores and supermarkets, its 26mm/s high-speed printing and auto cutter streamline checkout processes, reducing queues. Restaurants, cafes, and food trucks benefit from its dual Wi-Fi modes (AP & STA), enabling seamless order printing from kitchen displays or mobile POS systems. For hospitality businesses like hotels and event venues, the TP700 ensures quick ticket and receipt generation with professional precision. Delivery services and logistics providers can use its portable wireless capability for on-the-spot invoicing and proof of delivery. Additionally, pop-up shops, kiosks, and trade shows appreciate its compact design and hassle-free setup. With durable performance and versatile connectivity, the POSWAY TP700 is a top choice for any business needing efficient, high-quality receipt printing.



Restaurant



Coffee Shop



Bakery Shop



Icecream Shop



Intellectual Property Rights means any and all intellectual and industrial property rights throughout the world including rights in respect of or in connection with:

- a) any Confidential Information;
- b) Copyright;
- c) inventions (including patents);
- d) trade marks and service marks; and
- e) designs and circuit layouts,

whether or not now existing and whether registered or registrable and includes any right to apply for registration of such rights and includes all renewals and extensions;

License File means a coded binary file containing the Product, generated using a Redemption Code; Party means a Person who is party to this Agreement and their respective successors, trustees and permitted assigns;

Person means and includes any individual, corporation, trust, estate, partnership, joint venture, company, association, league, governmental bureau or agency, or any other entity regardless of the type or nature thereof;


Product means, individually and/or collectively, the software components, packages, usage rights and Documentation of the specified item.

Technical Support means and includes advice, training, information and other support regarding the selection, installation, maintenance, and application of the Products;

Territory means the territory in which the Distributor's rights under this Agreement apply, being the territory specified in Item 4, as varied by agreement between the parties from time to time;

TP700

Thermal Receipt Printer



Specifications

Resolution	203 DPI	
Printing method	Direct thermal	
Paper width	79.5±0.5mm	
Print width	72mm	
Column capacity	576 dots/line	
Printing speed	260 mm/s	
Interface	USB+Lan(USB+Lan+BT/WiFi)	USB+Serial+Lan (USB+Serial+Lan+BT/WiFi)
Line spacing	3.75mm (Adjustable by commands)	
Paper type	Continuous paper	
Paper thickness	0.06mm-0.08mm	
Paper width	80mm	
Paper roll outer diameter	80mm±0.5mm	
Character size	ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots) Simplified/Traditional Chinese:3.0×3.0mm(24×24 dots)	
Barcode Character		
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portugal) / PC863(Canadian) / PC865(Nordic) / West Europe / Greek / Hebrew /East Europe/ Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / PC858 / IranII / Latvian / Arabic / PT151(1251)	
1D Barcode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128	
2D Barcode	QR CODE / PDF417	
Input buffer	4096 Kbytes	
NV Flash	256 Kbytes	
Power		
Power adaptor	Input: AC 100~240V, 50 ~ 60Hz	
Printer Input	DC 24V/2.5A	
Cash drawer	DC 24V/1A	
Physical characteristics		
Weight	0.84 Kg	
Dimensions	152 × 134 × 125mm(D*W*H)	
Environmental Requirements		
Work environment	Temperature (0 ~ 45℃) humidity(10 ~ 80%)	
Storage environment	Temperature(-10 ~ 60℃) humidity(10 ~ 90%)	
Reliability		
Auto cutter	Partial	
Cutter life	1.5 million cuts	
Printhead life	150 km	
Software		
Emulation	ESC/POS	
Driver	Windows / Linux / Mac OS / Android	